ROBO-FIT, LLC

NYLON AIR BRAKE TUBING



NYLON AIR BRAKE TUBING



R

CONSTRUCTION	• Type A tubing consists of a single wall extrusion of pelletized homopolymer or copolymer of polyamide containing additives that provide heat and light resistance.
	• Type B tubing consists of a core extrusion with one or two layers of pelletized polyamide containing ad- ditives that provide heat resistance. The core is fiber reinforced using a spiral filament applied in each direction and sheathed with a protective layer of chemical resistant homopolymer or copolymer of poly- amide containing additives for heat and light resistance. The cover is fusion bonded to the core tube through the interstices of the spiral yarn reinforcement. The core tube and cover are of contrasting colors.
APPLICATIONS	•NAB150-Series polyamide tubing is for use in air brake systems. Non-reinforced tubing is designated Type A and reinforced tubing Type B. This tubing is intended for brake system connections that maintain a basically fixed relationship between couplings during vehicle operation.
	Air Tanks: Stores Air for Braking, Suspension, Sliders, etc.
	Air Brake Systems: Chassis (Provide Stopping Power for Truck/Trailer)
	Air Brake Systems: Brake Chamber (Provide Stopping Power for Truck/Trailer)
	Tire Inflation Systems: Keeps Tires at Optimal Pressure
	Air Ride Systems: Provides Air Suspension in Seat, Cab, and Vehicle
RANGES	•150 psig maximum (1030 KPa)
	•-40°F to +200°F (-40°C to +93°C)

ROBO-FIT, LLC

NYLON AIR BRAKE TUBING

Part No.:	Nominal O.D. (In)	Outside Dia. (In)	Inside Dia. (In)	Wall Thickness (In)	Min. Burst Pressure @ 73°F	Min. Bend Radius (In)	Max Stiffness (Ibs)
NAB150-2A	1/8"	.128/.122	0.079	.026/.020	1000	0.37	1
NAB150-2.5A	5/32"	.153/.159	0.092	.029/.035	1200	0.5	1
NAB150-3A	3/16"	.185/.191	0.118	.032/.038	1200	0.75	1
NAB150-4A	1/4"	.253/.247	0.17	.043/.037	1200	1	2
NAB150-5A	5/16"	.316/.308	0.232	.044/.036	1000	1.25	6
NAB150-6B	3/8"	.379/.371	0.251	.066/.058	1400	1.5	8
NAB150-8B	1/2"	.505/.495	0.376	.066/.058	950	2	20
NAB150-10B	5/8"	.630/.620	0.441	.097/.087	900	2.5	50
NAB150-12B	3/4"	.755/.745	0.566	.097/.087	800	3	80

Pr

R

COLOR	CODE	
BLACK	BK	
BLUE	BL	
BROWN	BR	
GREEN	GR	
ORANGE	OR	
PURPLE	PR	
RED	RD	
SILVER	SL	
TAN	TN	
YELLOW	YL	
WHITE	WT	

*Note that 1/8", 3/16", and 5/16" are Non DOT Sizes

Robo-Fit Example Part No.:	NAB150-6B-500-BK
oduct Description:	Nylon Air Brake Tubing, 3/8", Black, Type B, 500' Reel



EXTRUDED

IN USA

WARNING: This product can expose you to chemicals including Nickel and Nickel Compounds which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov