ROBO-FIT, LLC

NYLON AIR BRAKE TUBING



NYLON AIR BRAKE TUBING



R

| CONSTRUCTION | • Type A tubing consists of a single wall extrusion of pelletized homopolymer or copolymer of polyamide containing additives that provide heat and light resistance. |
|--------------|--|
| | • Type B tubing consists of a core extrusion with one or two layers of pelletized polyamide containing ad- ditives that provide heat resistance. The core is fiber reinforced using a spiral filament applied in each direction and sheathed with a protective layer of chemical resistant homopolymer or copolymer of poly- amide containing additives for heat and light resistance. The cover is fusion bonded to the core tube through the interstices of the spiral yarn reinforcement. The core tube and cover are of contrasting colors. |
| APPLICATIONS | •NAB150-Series polyamide tubing is for use in air brake systems. Non-reinforced tubing is designated Type A and reinforced tubing Type B. This tubing is intended for brake system connections that maintain a basically fixed relationship between couplings during vehicle operation. |
| | Air Tanks: Stores Air for Braking, Suspension, Sliders, etc. |
| | Air Brake Systems: Chassis (Provide Stopping Power for Truck/Trailer) |
| | Air Brake Systems: Brake Chamber (Provide Stopping Power for Truck/Trailer) |
| | Tire Inflation Systems: Keeps Tires at Optimal Pressure |
| | Air Ride Systems: Provides Air Suspension in Seat, Cab, and Vehicle |
| | |
| RANGES | •150 psig maximum (1030 KPa) |
| | •-40°F to +200°F (-40°C to +93°C) |

ROBO-FIT, LLC

NYLON AIR BRAKE TUBING

| Part No.: | Nominal O.D. (In) | Outside Dia. (In) | Inside Dia. (In) | Wall Thickness (In) | Min. Burst Pressure @ 73°F | Min. Bend Radius (In) | Max Stiffness (Ibs) |
|-------------|----------------------|----------------------|---------------------|------------------------|-------------------------------|--------------------------|------------------------|
| NAB150-2A | 1/8" | .128/.122 | 0.079 | .026/.020 | 1000 | 0.37 | 1 |
| NAB150-2.5A | 5/32" | .153/.159 | 0.092 | .029/.035 | 1200 | 0.5 | 1 |
| NAB150-3A | 3/16" | .185/.191 | 0.118 | .032/.038 | 1200 | 0.75 | 1 |
| NAB150-4A | 1/4" | .253/.247 | 0.17 | .043/.037 | 1200 | 1 | 2 |
| NAB150-5A | 5/16" | .316/.308 | 0.232 | .044/.036 | 1000 | 1.25 | 6 |
| NAB150-6B | 3/8" | .379/.371 | 0.251 | .066/.058 | 1400 | 1.5 | 8 |
| NAB150-8B | 1/2" | .505/.495 | 0.376 | .066/.058 | 950 | 2 | 20 |
| NAB150-10B | 5/8" | .630/.620 | 0.441 | .097/.087 | 900 | 2.5 | 50 |
| NAB150-12B | 3/4" | .755/.745 | 0.566 | .097/.087 | 800 | 3 | 80 |

Pr

R

| COLOR | CODE | |
|--------|------|--|
| BLACK | BK | |
| BLUE | BL | |
| BROWN | BR | |
| GREEN | GR | |
| ORANGE | OR | |
| PURPLE | PR | |
| RED | RD | |
| SILVER | SL | |
| TAN | TN | |
| YELLOW | YL | |
| WHITE | WT | |

*Note that 1/8", 3/16", and 5/16" are Non DOT Sizes

| Robo-Fit Example Part No.: | NAB150-6B-500-BK |
|-------------------------------|---|
| roduct Description: | Nylon Air Brake Tubing, 3/8", Black, Type B, 500' Reel |



EXTRUDED

IN USA

WARNING: This product can expose you to chemicals including Nickel and Nickel Compounds which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov