









INDUSTRIAL BALL VALVES

CONSTRUCTION	<ul style="list-style-type: none"> • CA360 Brass • CA377 Brass 	
APPLICATIONS	<ul style="list-style-type: none"> • Fuel Tank Shut-Off • Coolant Stop • Diverter Valves 	
RANGES	<ul style="list-style-type: none"> • Maximum Pressure 600 PSI • Temperature to 300° F • Saturated Steam 150 PSI 	

	FEATURES/BENEFITS
	<ul style="list-style-type: none"> • Forged Brass Body • Double O-Ring Stem Seal • Stem Seal Never Needs Tightening • 20,000 Leak Free Cycles • Blow Out Proof Stem • Made in USA 

NOTES

- Parts that include “PBF” are supplied as low lead compliant. 
- Part numbers without the “PBF” distinction are NOT lead free compliant.
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.



Double o-ring protection provides over 20,000 cycles without leakage!

The exclusive stem seal design that never needs tightening!



⚠ WARNING: Products offered by Robo-Fit, Inc. can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov

160BV MALE TO FEMALE BALL VALVE

PART NUMBER	MPT	FPT
160BV-L	3/8"	3/8"
160BV-P	1/2"	1/2"
160BV-R	3/4"	3/4"
160BV-S	1"	1"



120BV 3-WAY FEMALE BALL VALVE

PART NUMBER	FPT	CV
120BV-L	1/4"	5.2
120BV-N	3/8"	5.5
120BV-P	1/2"	5.5



Pressure Rating:


***Bottom Port as Inlet: 500 P.S.I.**

***Side Port as Inlet: 100 P.S.I.**



162BV FEMALE BALL VALVE

PART NUMBER	FPT	FPT
162BV-L	3/8"	3/8"
162BV-P	1/2"	1/2"
162BV-R	3/4"	3/4"
162BV-S	1"	1"



190BV 2-WAY 90° BALL VALVE

PART NUMBER	FPT	MPT	CV
190BV-L	1/4"	1/4"	5.2
190BV-N	3/8"	3/8"	5.5
190BV-P	1/2"	1/2"	5.5



Pressure Rating:

***Bottom Port as Inlet: 600 P.S.I.**

***Side Port as Inlet: 100 P.S.I.**



MADE IN USA