

PUSH BUTTON VALVES

CONSTRUCTION	•CA377 Brass	
APPLICATIONS	<ul style="list-style-type: none"> •Fuel Sampling Valve •Pressure Relief •Valve Injection •Drain Valve •Holds Vacuum 	
RANGES	<ul style="list-style-type: none"> •Maximum Pressure : 500 PSIG •Temperature: -40° to 300° F (Standard) -40° to 400° F (Special) 	

FEATURES/BENEFITS
<ul style="list-style-type: none"> •Instantaneous On/Off •Multiple O-Ring Options •Flexible End Connection •Forged Brass Body •90° Configuration •Made in USA •Guaranteed Quality


PB2 FPT x FPT

PART NUMBER	FPT	FPT	STYLE	OPERATOR
PB2-J	1/8"	1/8"	STANDARD	PUSH BUTTON
PB2-3A-J	1/8"	1/8"	PANEL MOUNT	PUSH BUTTON
PB2-L	1/4"	1/4"	STANDARD	PUSH BUTTON
PB2-3A-L	1/4"	1/4"	PANEL MOUNT	PUSH BUTTON

⚠ WARNING: Products offered by Robo-Fit, Inc. can expose you to chemicals such as lead, a chemical which is known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Closed Position Shown
 Push Button Toward the Valve
 Body for Sampling



MADE IN USA